Directions for Use

For Drill Collars & Tool Joints – Apply Drill Tek with a swab applicator or by hand.

Drill Tek can also be applied by brush. Can be applied in temperatures below freezing to 0°F. Coverage of product must be determined by API standards or drill pipe/connections manufacturer.

Not For Use On Oxygen Lines

HMIS Codes	
Health	0
Flammability	1
Reactivity	0
Personal Protection	В

P.I.N - G - 190 To reorder call: 1-877-703-3044 or 281-944-4777





DRILL TEK

THREAD & JOINT COMPOUND

NLGI - 1

ASTM Penetration Unlocked @ 77°F 210 - 330
Adheres to Wet Joints
Protects Against Galling & Seizing
Superior Resistance to Makeup Downhole
Contains Rust & Oxidation Inhibitors Resistant
Temperature Range - 0°F - 550°F
Improves Coefficient of Friction Under
Extreme Workload Conditions
DOES NOT CONTAIN LEAD

Keep Out of Reach of Children

Encore Industrial Products, LLC PO Box 300, Barker, TX 77413 281-944-4777 or 1-877-703-3044

Drill Tek Thread & Joint Compound

Sets the standard for durability & stability under adverse conditions. This specialized oilfield compound protects against severe circumbient makeup downhole through raising the coefficient of friction during extreme workload conditions. Fortified with rust and oxidation inhibitors along with specialty stabilizers to safeguard against H2S contamination downhole.

Drill Tek prevents leakage of API round thread casing and tubing joints under pressure as high as 10,000 PSI. Safe to brush on pipe joints in cold weather.

Warranty

Encore Industrial Products, LLC warrants our product to be free of manufacturing defects. Liability for product proven defective, if any, is limited to replacement of defective product or refund of the purchase price paid for the defective product as determined by Encore Industrial Products, LLC. No other warranty or guarantee of any kind is made by Encore Industrial Products, LLC expressed or implied, statutory, by operations or law or otherwise including merchantability and fitness for a particular purpose.

www.encoreindustrial.com