Directions For Use

Annearance

For Grease Tubes – Follow directions on grease gun for loading instructions. To insure proper service pump out any existing grease prior to applying or pumping Encore Industrial's Marine Tek Industrial Water Resistant Grease.

For Pails & Drums – Follow directions indicated on the grease pump for proper use.

Green smooth

Appearance	Green, smooth
NLGI	2
Penetration	265-295
(ASTMD217)	
Worked penetration	265-295
60x (ASTM D217)	
Base oil	Mineral oil
Base oil viscosity	143 cSt at 40°C
Base oil viscosity	11 cSTat 100°C
Base oil viscosity index	40
Base oil pour point	-10°F (-23°C)
Thickener	Calcium sulfona
complex	
Specific gravity	0.9
Density (lb/gal)	7.5
Dropping point	>550°F (288°C)
(ASTM D566)	
Flash point	430°F (221°C)
Temperature range	0°F – 450°F (-
18°C - 232°C)	
Four-ball wear	0.6 mm
(ASTM D2266)	
Four-ball EP weld point	620 kgf
(ASTM D2596)	
Load-wear index	80
(ASTM D2596)	
Timken OK	65lbs



MARINE

TEK

INDUSTRIAL WATER RESISTANT GREASE

NLGI - 2

TimKen Ok Load – 65 LBS Fourball EP (kg-f) 500/ Fourball Wear Scar (mm) 0.6

ASTM Dropping Point 550° F (290° C) Penetration / ASTM D-217 265-295

OFFSHORE RATED

Keep Out of Reach of Children

Net Wt. 5LB

Marine Tek sets the standard for durability & stability under adverse conditions. This industrial water resistant grease protects against damaging water wash out. This unique formula is fortified with an EP extreme pressure package for high pressure service applications. Superior rust and oxidation stabilizers help extend equipment service life. Ideal for salt water and fresh water applications

First Aid Information

Read SDS for complete information

Eye Contact – Flush eyes with clean water for at least 15 minutes. If irritation occurs call a physician. Skin Contact – Wash skin with soap and water, if irritation occurs, call a physician. Ingestion – Do not induce vomiting and give large quantities of water. Call a physician immediately if stomach pains or nausea occur.

MADE IN THE USA

P.I.N - G - 140 Encore Industrial Products, LLC PO Box 300, Barker, TX 77413 281-944-4777 or 1-877-703-3044