

Moly Bond 007

Moly Bond 007 is an ultra-advanced formula created to meet the high demands of the oil & gas industry. **Moly Bond 007** is developed to stand up to the fluctuating environments & conditions for all types of oil field tools. This product can withstand exposure to varying temperatures, RPM's, extreme pressure, and long continuous run times. **Moly Bond 007** resists acids, oils, caustics, and water.

Highlights:

Use at Pre-Assembly	Coats evenly
High Thermal Range	Prevents Fretting
Fast Cure Formula	Prevents Seizing
Reduces Torque	Prevents Galling
Bonds to Ferrous & Non Ferrous metal	Repels Dust & Dirt
	Extends Service Life

Designed to be used on:

Drill Collars	Pipe Threads
Bolts	Open Chains
Shackles	Sleeves
Dies	Taps
Sprockets	Swivels
Cables	Gears
Pulleys	Shafts
Slides	etc.

Made In USA

www.encoreindustrial.com

**FORMULATED FOR
MUD MOTOR SHOPS**

P.O. Box 100

Encore Industrial Products, LLC

P.O. 300, Barker, TX 77413

281-944-4777 or 1-877-703-3044



MOLY BOND 007

Molybdenum Disulfide Lubricant

**High Thermal Range
-110°F to 1100°F**

**No Chlorinated
Solvents**

Ultra Fast Dry Formula

**Superior Molecular
Bond**

**Extreme Pressure Loads
to 100,000 PSI**

DANGER

**EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.
KEEP OUT OF REACH OF CHILDREN.**

Read carefully other cautions on side panel.

Net Wt. 11 oz (312 grams)

Directions For Use:

Step 1: Make sure application surface is free from dirt, loose rust, oil, old paint and grease.

Step 2: Shake can well enough to rattle internal mixing ball. Shake can for about 15 seconds.

Step 3: Position can 8 to 10 inches from surface. Spray in a sweeping motion to produce a thin uniform coating.

Step 4: Allow first coat to dry 5 minutes before applying a second coat.

Step 5: Turn can upside down and spray a 2 second shot burst to clear chamber.



Read Safety Data Sheet Before Using

DANGER

May cause drowsiness or dizziness. Causes mild skin irritation. Causes serious eye irritation. May cause genetic defects. Extremely flammable aerosol. Pressurized container. May burst if heated. May be harmful if swallowed.

Precautionary Statements: Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.

First Aid: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/Doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention if exposed or concerned. Get medical advice/attention.

Emergency Phone Number: CHEMTREC US: 1-800-424-9300
INTERNATIONAL CALLS: 1-703-527-3887

LB2-4155 Moly Bond 007 GHS v.4	LAM	Initial Approval	Date: 08.01.18
Label Size: 5.875 x 8.625	LAM	Initial Approval	OK to Print: <input checked="" type="checkbox"/>
Can Size: 211 x 604 SW (.4375 OL)	LAM	Initial Approval	Changes Requested New Proof <input type="checkbox"/>
Color(s): PROCESS	LAM	Initial Approval	
ALL AREAS NEED INITIAL APPROVAL — ALL CHANGES IN WRITING ONLY			