

DIRECTIONS FOR USE

- Step 1:** Follow dilution chart to determine proper dilution rate.
- Step 2:** Wear proper PPE prior to using TRC – XL as per SDS.
- Step 3:** Thoroughly wet equipment with water to prepare surface to be cleaned.
- Step 4:** Apply TRC – XL through a pressure washer or using a chemical sprayer. Agitate to help penetrate heavy buildup as necessary. Let stand for up to 5 minutes.
- Step 5:** Rinse and let dry.

APPLICATIONS & DILUTIONS

Frac Tanks	1 to 10 water
Concrete Floors	1 to 25 water
Engines	1 to 10 water
Machinery	1 to 12 water
Machine Sumps	1 to 12 water
Metal Surfaces	1 to 50 water
Plastics	1 to 12 water
Power Units	1 to 14 water
Stainless Steel & Aluminum	1 to 40 water
Tools	1 to 2 water
Mud Pumps	1 to 12 water
Draw Works	1 to 12 water
Substructure	1 to 12 water
Traveling Block	1 to 12 water
Hook & Swivel	1 to 12 water
Drilling Rig Floor Etc.	1 to 12 water
Dozers	1 to 14 water
Back Hoes	1 to 14 water
Fork Lifts	1 to 20 water
Vac Trucks	1 to 11 water
Industrial Filters & Screens	1 to 10 water
Valves & Pumps	1 to 12 water

CONTAINS: Caustic Soda, (CAS No) 1310-73-2; sodium xylenesulfonate, (CAS No) 1300-72-7

HMI S Codes	
Health	2
Flammability	0
Reactivity	0
Personal Protection	B

P.I.N.-A-125



TRC-XL TOTAL RIG CLEAN EXTRA STRENGTH

- Fortified with Nonionic Detergents & Aqueous Based Solvents
- Breaks Down Heavy Duty Diesel Carbon and Petroleum Build Up
- Contains Enhanced Wetting Agents for Deep Cleaning



DANGER

KEEP OUT OF REACH OF CHILDREN

See side panel for additional precautions and First Aid.



- NET CONTENTS:**
- 5 Gallons
 - 20 Gallons
 - 35 Gallons
 - 55 Gallons



DANGER
May be corrosive to metals
Causes severe skin burns
and eye damage
Causes serious eye damage



PRECAUTIONS

Keep only in original container. Do not breathe vapours, spray, mist. Wash hands thoroughly after handling. Wear eye protection, protective gloves. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor. Specific treatment (see First Aid measures on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Dispose of contents/container to an approved waste disposal plant.

FIRST AID

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). **After Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a doctor/physician. **After Skin Contact:** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a doctor/physician. **After Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician. **After Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a doctor/physician.

FIREFIGHTING

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

SAFE HANDLING

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not breathe vapours, spray, mist. Avoid contact during pregnancy/while nursing.



Encore Industrial Products, LLC
PO Box 300
Barker, TX 77413-0300
281-944-4777 or 1-877-703-3044