


## CORE GUARD EL

### Product Highlights

This proprietary formula creates a unique thick foam that breaks the surface tension as the foam breaks for deep penetration.

**CORE GUARD EL** provides supreme protection from friction and corrosion.

Performs under extreme service conditions which can extend the service life of equipment. Use **CORE GUARD EL** on a regular maintenance schedule basis for optimum protection and performance.



**P.I.N. G-110**

### ENCORE INDUSTRIAL PRODUCTS, LLC

P.O. Box 300  
Barker, TX 77413  
281-944-4777  
or 1-877-703-3044  
www.encoreindustrial.com



# CORE GUARD EL

## Foaming Wire Rope Treatment

### Espuma tratamiento alambre cuerda

Fortified With Molybdenum Disulfide

Fortificado con disulfuro de molibdeno

Ultra High Temp In Service Rating to 400F

Temperatura ultra alta calificación en el servicio a 400F

Performs Under Extreme Pressure Service Loads

Lleva a cabo bajo extremas cargas de presión de servicio

Core Protection To Increase Cable and Wire Rope Life

Core protección a aumentar la vida del cable y vable de acero

Resistant To Water Washout

Resistente al lavado por agua

Developed For Onshore/Offshore Extreme Element Protection

Desarrollado para onshore/offshore elemento de protección extrema

**KEEP OUT OF REACH OF CHILDREN**

MANTENER FUERA DEL ALCANCE DE LOS NIÑOS

#### WARNING:

EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER  
MAY BURST IF HEATED.

#### ADVERTENCIA:

AEROSOL EXTREMADAMENTE INFLAMABLE. CONTENEDORES A  
PRESIÓN PUEDEN EXPLOTAR SI SE CALIENTAN.

NET WT. 16 OZ. (453 grams)

### Directions For Use

- STEP 1. Shake can vigorously for one minute after mixing ball begins to rattle.
- STEP 2. Spray 8-10 inches from surface.
- STEP 3. Allow to penetrate.
- STEP 4. Second coat gives additional protection.

### Precautionary Statement

Contains Mineral Oil, Petroleum Distillates, Solvent-Dewaxed Heavy Paraffinic (CAS#64742-65-0), Propane (CAS#74-98-6), Butane (CAS#106-97-8), Isobutane (CAS#75-28-5), Molybdenum (IV) Sulfide (CAS#1317-33-5). If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Read Safety Data Sheet before using.

Made in U.S.A.

VOC Content: 19.5%

**FOR PROFESSIONAL USE ONLY**

### HMIS RATING:

Health	1
Flammability	2
Reactivity	0
Personal Protection	B



#497255

10/15

4cp

#497255ENCIN-P20