

D-Limonext

DEGREASER • DEODORIZER • DECLOGGER

SPOT, GUM & TAR REMOVER

100% Natural • Biodegradable • Phosphate Free •
No Petroleum Distillates

FOR GENERAL CLEANING and DEODORIZING: Dilute 4 to 8 oz. of concentrate per gallon of warm water. Sponge or spray onto surface and allow to stand a few moments. Wipe with clean cloth or sponge, rinse well.

FOR TOILETS, SINKS, URINALS, SHOWER STALLS, BATHTUBS, CHROME FIXTURES AND CERAMIC TILES: Dilute 4 to 8 oz. per gallon and apply to surface and allow to stand a few moments. Rinse away all soap film and scale.

MACHINERY, ENGINES, RUBBER BURNS, GRAFFITI and HEAVY INDUSTRIAL CLEANING: Dilute concentrate 16 oz. per gallon of warm water. Mop, spray or sponge onto surface and allow to stand at least 5 minutes. Scrub or brush thoroughly and rinse with clean water.

GREASE TRAPS, DRAIN MAINTENANCE AND DECLOGGING: Add 8 oz. weekly to all drain openings and let stand 10 minutes flush with warm water. For grease traps under 20 cu. ft., add 5 oz. daily. Use more for larger traps. For clogged drains, pour 12 to 16 oz. into drain.

FOR TAR and ASPHALT REMOVAL: Apply concentrate directly. Allow 2 to 4 minutes, agitating if necessary. Rinse with clear water.

FOR ODOR CONTROL AROUND DUMPSTERS, GARBAGE DISPOSALS, SEPTIC TANKS, KENNELS, ETC.: Dilute 4 ounces of concentrate per gallon of water. Spray or mop onto area to be treated and allow to stand. Around sewage treatment plants apply by the drip method or fogging. Product may be sprayed or fogged into the air if desired.

RUG AND UPHOLSTERY SPOT REMOVAL: Apply concentrate with cloth to affected area and blot. For gum removal, blot directly on gum. Allow to work 2-3 minutes. Use a scraper to remove gum. Always test on an inconspicuous area of fabric before applying.

NOTE: Pretest all plastic surfaces prior to use.

P.I.N. -I-170



Bio Engineered & Emulsifying Agent
Cleaner/Degreaser

Removes Grease, Tar, Oil & Gum

Clears Drains & Grease Traps

Fresh Citrus Scent

Professional Grade

Shock Treatment for Grease Traps

No Petroleum Distillates



WARNING

Combustible Liquid
Causes Skin Irritation

May Cause Allergic Skin Reaction
Keep out of reach of children.

See side panel for additional precautions and First Aid.

NET CONTENTS: 4x1 5 Gallons
 20 Gallons 30 Gallons
 55 Gallons

Contains Powerful Citrus Solvents

Wipes out grease and grime on a wide variety of surfaces. Fantastic, naturally fresh citrus scent. Incredibly versatile.

Use on floors, drains, autos, boats, etc.

Non-acidic

Precautions

Keep away from open flames, heat, sparks. No smoking. Avoid breathing mist, spray, vapors. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection and protection and protective gloves.



If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention. Take off contaminated clothing and wash before reuse. See FIRST AID below.

In case of fire: Use suitable extinguishing media to extinguish. Store in well-ventilated place. Keep cool. Dispose of contents/container to an approved waste disposal plant. Firefighting Instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Suitable extinguishing media: Foam, dry powder, carbon dioxide, water spray, sand.

FIRST AID

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. (Show label where possible.)

Inhalation: Allow victim to breath fresh air. Allow victim to rest. **Skin Contact:** Remove affected clothing and wash all exposed skin area with soap and water. If skin irritation occurs, get medical attention. **Eye Contact:** Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist. **Ingestion:** Rinse mouth. DO NOT induce vomiting. Obtain emergency medical attention.

Precautions for Safe Handling

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measure against static discharge. Use only non-sparking tools. Avoid breathing mist, spray vapors.

For Emergencies, Call ChemToll: 800-255-3924



Encore Industrial Product, LLC

3502 Bacor Rd.
Houston, TX 77084
281-944-4777
or 1-877-703-3044

www.encoreindustrial.com

FOR PROFESSIONAL USE ONLY