

Finish 1st is formulated for high traffic environments. Hospitals, airports, office buildings, universities and schools are ideal for this high solids slip resistant floor finish. When durability and detergent resistance is required, **Finish 1st** is the perfect choice for composition, marble and marble floor maintenance.

WARNING: Harmful if swallowed. Causes skin irritation. Harmful to aquatic life with long-lasting effects.



PRECAUTIONARY STATEMENTS



Prevention: Keep container tightly closed. Keep in original container. Keep cool. Avoid breathing mist, vapors or spray. Do not get into eyes, on skin or on clothing. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use in a well ventilated area. Avoid release to the environment. Wear protective gloves and eye protection. Read Safety Data Sheet carefully before handling.

First Aid:

If Swallowed: Call a doctor if you feel unwell. Rinse Mouth. Do NOT induce vomiting.

If In Eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

If On Skin: Wash with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

If Inhaled: Remove person to fresh air and keep comfortable for breathing. Call doctor if person feels unwell. If any irritation persists, get immediate medical attention. In case of fire: Use water spray, alcohol resistant foam, carbon dioxide (CO₂) or dry chemical to extinguish.

Storage: Store in a well-ventilated place. Protect from sunlight. Keep from freezing. Store at temperatures 45-90° F

Disposal: Dispose of contents and container to an approved waste disposal plant in accordance with applicable local, state, federal and international regulations.



Meets ASTM D-2047-72 Testing Standards

Bufs to High Gloss

Seals in One Coat

Non-Yellowing & Detergent Resistant

Reduces Strip Cycles

Guards Against Powdering

Helps Resist Scuffs & Marks

Caution: Keep out of reach of children

See side panel for additional precautions and first aid.

Precaución: Mantener fuera del alcance de los niños ver el panel lateral para las precauciones adicionales y primeros auxilios.

Net Contents:

- 5 Gallons 20 Gallons
- 30 Gallons 55 Gallons

Directions for Use:

Pre – Floor Preparation – Make sure the floor is completely clean of sand, dirt and old floor finish prior to applying product. Use **Express Strip** or **Express Strip Max**, product code P.I.N J – 140 or P.I.N. F-105 for heavy build up removal. Make sure the floor surface is neutralized to a 7 range PH before applying product. A neutral PH will allow for optimum adhesion of **Finish 1st** to your flooring surface. The floor surface must be completely dry prior to applying product.

Application:

Apply **Finish 1st** in thin uniform coats; allow each layer to dry for 30 minutes. Average coverage is 2000 to 3000 square feet per gallon depending on floor material type, age and product application.

Maintenance:

Sweep Floor on daily basis and pick up all sand, dirt and debris. Damp mop with a properly diluted neutral cleaner to maximize floor finish performance.

For Professional Use Only

P.I.N. – F-110



Encore Industrial Products, LLC
3502 Bacor Rd., Houston, Tx 77084
281-944-4777 / 1-877- 703-3044
www.encoreindustrial.com