

Directions for Use

For Grease Tubes – Follow directions on grease gun for loading instructions. To insure proper service pump out any existing grease prior to applying or pumping **Encore Industrial's Green Tek High Impact Grease.**

For Pails & Drums – Follow directions indicated on the grease pump for proper use.

HMIS Codes	
Health	0
Flammability	1
Reactivity	0
Personal Protection	B

P.I.N - G – 130



**GRAY TEK
STANDARD DAILY
LUBE**

NLGI Rating – 2
Color Gray
Temperature Rating – -10°-350° F
Moisture Resistance – Excellent
Metal Adhesion - Excellent
Contaminant Resistance - Excellent

Keep Out of Reach of Children

Net Contents: 120 LB KG

Encore Industrial Products, LLC
PO Box 300, Barker, TX 77413-0300
281-944-4777 or 1-877-703-3044

Gray Tek Standard is an ideal grease when daily lubrication is required. Excellent moisture and containment resistance. **Gray Tek** has great adhesive properties and remains stable under normal service conditions.

First Aid Information

Read MSDS for complete information

Eye Contact – Flush eyes with clean water for at least 15 minutes. If irritation occurs call a physician.

Skin contact – Wash skin with soap and water, if irritation occurs, call a physician.

Ingestion – Do not induce vomiting and give large quantities of water. Call a physician immediately if stomach pains or nausea occur.

To reorder call:

1-877-703-3044 or 281-944-4777

