

Directions for Use

For Grease Tubes – Follow directions on grease gun for loading instructions. To insure proper service pump out any existing grease prior to applying or pumping **Encore Industrial's Green Tek High Impact Grease**.

For Pails & Drums – Follow directions indicated on the grease pump for proper use.

HMIS Codes	
Health	0
Flammability	1
Reactivity	0
Personal Protection	B

P.I.N - G – 160 35LBP



GREEN TEK HIGH IMPACT GREASE

Timken Load – 65
NLGI Rating – 2.0-2.5
Temperature Rating – 500+ Degrees (Non-Melt)
Extreme Tacifier Package – Excellent Adhesive & Cohesive Properties
Penetration (ASTM – D – 217) - 245-265 mm
4-ball weld test – 315 minimum
Water Resistance – Excellent
Extreme Pressure Rated – Extreme PSI Rating

Keep Out of Reach of Children

Net Contents: 35 LBS

Encore Industrial Products, LLC
PO Box 941119, Houston, TX 77094
281-944-4777 or 1-877-703-3044

Green Tek High Impact Grease provides high impact protection. This product helps resist against “pound out”, “splatter out” from vibration and jarring.

First Aid Information

Read MSDS for complete information

Eye Contact – Flush eyes with clean water for at least 15 minutes. If irritation occurs call a physician.

Skin contact – Wash skin with soap and water, if irritation occurs, call a physician.

Ingestion – Do not induce vomiting and give large quantities of water. Call a physician immediately if stomach pains or nausea occur.

To reorder call:

1-877-703-3044 or 281-944-4777

