


HYPER SEAL

Product Highlights

An advanced next generation industrial rubberized specialty coating. Designed to be used for industrial and institutional applications. Stops rust and corrosion on virtually any surface. Seals and secures open seams and separations on buildings and equipment.

DESIGNED TO BE USED ON:

- Condensate Pans • Battery Trays
- Gutters • Downspouts • Seal Holes
- Seal Cracks • Trailers • Truck Beds
 - Window Seams • Kick Plates
 - Storage Tanks • Cat Walks
- Diamond Plate • Mower Decks
- Nuts and Bolts • Wood Preserver
 - Sound Proof Applications
 - Tree Wound Dressing
- Concrete Crack Sealer, Etc.



P.I.N. I-110

ENCORE INDUSTRIAL PRODUCTS, LLC

P.O. Box 300
Barker, TX 77413
281-944-4777
or 1-877-703-3044
www.encoreindustrial.com



HYPER SEAL

Industrial Rubberized Specialty Coating

Especialidad de revestimiento de goma

Seals Out Moisture
Las juntas de humedad

Quick Drying Formula
Fórmula de secado rápido

Paintable Coating
Pintable revestimiento

Will Not Crack Or Chip
No se agrietan o chip

Adheres To Most Types Of Surfaces
Se Adhiere a la mayoría de las superficies

KEEP OUT OF REACH OF CHILDREN
MANTENER FUERA DEL ALCANCE DE LOS NIÑOS

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR. EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

PELIGRO: LÍQUIDO ALTAMENTE INFLAMABLE Y EL VAPOR. AEROSOL EXTREMADAMENTE INFLAMABLE. CONTENEDORES A PRESIÓN PUEDEN EXPLOTAR SI SE CALIENTAN. PUEDE CAUSAR SOMNOLENCIA O MAREOS. PUEDE CAUSAR DAÑOS A LOS ÓRGANOS A TRAVÉS DE UNA EXPOSICIÓN PROLONGADA O REPETIDA. PUEDE SER FATAL SI SE INGIERE Y ENTRA EN LAS VÍAS RESPIRATORIAS. CAUSAN IRRITACIONES EN LA PIEL. SOSPECHOSOS DE DAÑAR LA FERTILIDAD O EL FETO.

NET WT. 16 OZ. (1 LB.) (453 grams)

Directions For Use

Shake can vigorously for one minute after mixing ball begins to rattle. Apply to clean dry surface not under 50°F. Spray with short even strokes from 14-18 inches.

Precautionary Statement

Contains Calcium Carbonate (CAS#471-34-1), Bitumens (CAS#8052-42-4), Toluene (CAS#108-88-3), Medium Mineral Spirits (CAS#64742-88-7), Propane (CAS#74-98-6), Butane (CAS#106-97-8), Isobutane (CAS#75-28-5). If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. In case of fire: Use water fog, dry chemical or carbon dioxide to extinguish. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get Medical advice/attention if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Keep cool. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations. IMPORTANT: Avoid application of any undercoating and/or rust-proofing materials closer than 12 to 14 inches to the exhaust system and "catalytic converter." WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Read Safety Data Sheet before using.

Made in U.S.A.

VOC Content: 39%

FOR PROFESSIONAL USE ONLY

HMIS RATING:

Health	1
Flammability	3
Reactivity	0
Personal Protection	B



#496405

10/15

4cp

#496-405ENCIN-P20