PRECAUCIÓN: Si no puede leer en ingles, pregunte a su supervisor sobre las instrucciones para el uso apropiado antes de trabajar con este producto.

An acrylic polymer floor finish that provides a natural looking low gloss protection against foot traffic, abrasion and scuffing on stone and tile flooring. This product can be applied and reapplied with ease and is repairable without redoing the entire floor.

DIRECTIONS

INITIAL APPLICATION

- 1. Remove all old wax and floor finish with appropriate stripper.
- 2. Rinse the floor thoroughly (at least twice) with clean water.
- 3. Repeat steps 1-2 if all finish is not removed. Allow floor to dry.
- 4. Apply 3-4 thin coats of this product using a clean synthetic mop, allowing a minimum of 30 minutes between coats.
- 5. Apply additional coats in the same manner, allowing at least 30 minutes drying time between coats.
- 6. For very porous floors, an initial coat of floor sealer is recommended.

NOTE: Temperature, humidity and air movement affect curing time.

To avoid contamination, do not return any unused material to original container.

ROUTINE MAINTENANCE

- 1. Sweep or dust mop as necessary.
- 2. Damp mop with proper cleaner following label instructions. For accumulated soil, lightly scrub as needed.
- 3. After cleaning, spray buffing or burnishing may also be done once loose dirt and dust has been swept up.
- 4. Additional coats may be applied if needed.

FOR PROPER PERFORMANCE USE ONLY WHEN PRODUCT TEMPERATURE AND FLOOR TEMPERATURE ARE 50°F OR HIGHER.

WARNING: Do not allow wet floor areas to be open to foot traffic. Wet shoes or wet spots can create a slippery condition. Wet floor areas should be cordoned off until dry for traffic.

Coverage: 2,000-2,500 square feet per gallon.



Encore Industrial, LLC 3502 Bacor Road Houston, Texas 77084 www.encoreindustrial.com 1-877-703-3044

Floor Care Finish Cera de Piso



ProtectMatte Floor Finish

Cera de Brillo Minimal

- Durable
 Scuff Resistant
- Natural Low Gloss Protection



Not a Dangerous Substance or Mixture according to the (GHS) Globally Harmonized System of Classification and Labeling of Chemicals

CONTAINS: Water (7732-18-5), Acrylic Polymer (Not Listed), Polyethylene Emulsion (Mixture), Dipropylene Glycol Monomethyl Ether (34590-94-8), Diethylene Glycol Monoethyl Ether (111-90-0), tris(2-butoxyethyl)phosphate (78-51-3).

FIRST AID: Inhalation: Allow victim to breathe fresh air. Allow the victim to rest Skin: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse Eyes: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention

HMIS III Rating: Health: 1 Slight Hazard **Flammability:** 0 Minimal Hazard **Physical:** 0 Minimal Hazard **Personal Protection:** B

KEEP OUT OF REACH OF CHILDREN
KEEP FROM FREEZING
INDUSTRIAL AND INSTITUTIONAL USE ONLY



