

RUST REDUX XL

Product Highlights

RUST REDUX XL provides the ultimate solution for rust and corrosion on metal. Utilizing a new molecular process that absorbs rust molecules and forms a rust-free black barrier surface. It's the perfect choice as a base primer coat over rusted metal surfaces. Surfaces protected with this primer and an oil-based paint system resists the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.

Directions For Use

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: Shake or stir well before using. **RUST REDUX XL** is ready-to-use. Do not dilute. Apply this product using a brush or roller. Apply a second coat to ensure complete transformation of rusty surfaces.

COVERAGE: 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

IMPORTANT:

DO NOT RETURN UNUSED MATERIAL TO ORIGINAL CONTAINERS.



Transformador de Oxido

Chemically Converts Rust Molecules Through Absorption
Químicamente convierte las moléculas de óxido a través de la absorción

Creates a Black Rust Resistant Barrier on Ferrous Metal
Crea un negro barrera resistente a la corrosión en metales ferrosos

Protect Against Future Rust Growth
Protege contra el futuro crecimiento de moho

Perfect For Base Primer Coat or Use as a Finish Coat
Perfecto para capa base de imprimación e el uso como capa de acabado.

Extends Metal Surface Service Life
Extiende la vida útil de la superficie de metal

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

CAUTION

May cause eye and skin irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID:

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician. **IF ON SKIN:** Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician. **IF SWALLOWED:** DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Contact a physician or poison control center immediately. **IF INHALED:** Move person to fresh air. If irritation is persistent, contact a physician.

See MSDS for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Product should be used within 9 months of purchase. Do not apply this product if the surface temperatures are below 50°F. Keep container tightly closed when not in use. Store in a cool, dry place, protected from freezing or temperatures above 100°F. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

Read the Material Safety Data Sheet before using.

Made in the U.S.A.

INGREDIENT(CAS Number): **Proprietary Polymer**
(No CAS #); **Water** (7732-18-5); **Tannic Acid**
(1401-55-4); **2-Butoxyethanol** (111-76-2);
Oxalic Acid (6153-56-6).

NFPA® RATINGS
FLAMMABILITY

HEALTH  REACTIVITY

SOLD BY:

ENCORE INDUSTRIAL PRODUCTS LLC
PO Box 300 • Barker, TX 77413
281-944-4777 or 1-877-703-3044



P.I.N I-260