### ISO Grade 68

Encore way lube oils are formulated Proprietary friction modifiers make for improved machine performance during slow moving heavily loaded machine runs.

### Great for use in the slideways of the following machines:

- Horizontal Boring Machine
- Shapers
- Milling Machines

- Jig Borers
- Planers
- Grinders

#### **FOR USE**

For use as a medium viscosity slideway lubricant.

#### P.I.N. G-255

Health	1
Flammability	1
Reactivity	0
Personal	Α

Batch Number: #





ISO GRADE 68

### **Decreases Machine** Chatter

**Extreme Pressure Formula** 

## **Fortified To Protect Against Rust**

**Provides Superior Fluid Adhesive** 

# **Excellent Fluid Separation from H20**

### **Reduces Stick Slip Production Runs**

Keep Out of Reach of Children

**Net Contents** 

☐ 30 Gallons ☐ 55 Gallons

□ 275 Tote

#### First Aid

Inhalation: Vapors generated at high temperatures (only) or oil mist may cause mild irritation of the nose, throat and respiratory system. Consult physician and poison control immediately.

**Eye Irritation:** May cause minimum eye irritation. Consult physician and poison control immediately.

**Skin Contact:** May cause minimum skin irritations, long term heavy exposure may dry or defat the skin. May also cause dermatitis or oil acne. High pressure injection under the skin could cause extensive tissue damage. Consult physician and poison control immediately. **Ingestion:** If swallowed may be slightly toxic. Consult physician and poison control immediately.

Dispose of in accordance with local, state and federal regulations.



Warning: Harmful if inhaled. Avoid breathing dust/fumes/gas/mist/spray. Use only outdoors or in a well-ventilated area.