

AIR WASH

Helps Address
H₂S Emissions

Neutralizes the Air

Air Purification Treatment

Lasts Up to 90 days
Semisolid Gel

**INFUSED WITH ACTIVATED CARBON FOR
ADVANCED ODOR ABSORPTION**

EASY TO USE

1. Turn product upside-down.
2. Remove the bottom container from the top lid, so semisolid gel is sitting on lid.
3. Place lid and exposed semisolid gel in the desired location

USE IN:

**RETURN AIR DUCTS,
VEHICLES, TRASH ROOMS,
EXTERIOR/INTERIOR LIFT
STATION AREAS,
RESTROOMS, CLOSETS,
STORAGE ROOMS,
OUTDOOR RESTROOMS,
ETC.**

SIZES: 1 LB. & 35 LB.



Manufactured By
Encore Industrial Products
www.encoreindustrial.com
(281)-944-4777

3502 Bacor Rd Houston, TX 77084

AIR WASH

AIR WASH will significantly reduce foul odors and H₂S gas in confined spaces like manholes, lift stations, grease traps and air handlers of all sizes.

Foul Odor and H₂S Gas Absorbent

AIR WASH...

- Is Easy-To-Use
- Is an Activated Carbon Based Product
- Absorbs H₂S Gas and Foul Odors
- Works Quickly
- Is Non-Flammable
- Is Long-Lasting, Working From 2-5 Months



AIR WASH is ideal for use in lift stations, manholes and air handlers where H₂S is a problem. Actual customer applications in manholes have reduced the amount of H₂S present from 200 parts per million to non-detectable in 15 minutes, quickly changing the work environment from unpleasant to pleasant.

DIRECTIONS:

FOR LIFT STATIONS:

Remove the lid off the pail in order to begin activation of **AIR WASH**. The pail is suspended above the high water level in the lift station. For low H₂S levels one pail is suspended about 1 foot below the lift station lid. In medium H₂S levels a second pail is suspended 2-4 feet above the high water level. In heavy H₂S levels 3 or more pails are suspended above the high water level. In extreme H₂S conditions call for technical support

FOR MAINS and MANHOLES:

Remove the lid off the pail in order to begin activation of **AIR WASH**. The pail is suspended above the water level just below the manhole lid. For low levels of H₂S the pail is suspended 6-12 inches below the manhole lid. For heavier H₂S levels more than one pail may be required and should be suspended 3 feet below the pail above it. In severe H₂S applications, call for technical support

FOR GREASE TRAPS and SUMPS:

Remove the lid off the pail in order to begin activation of **AIR WASH**. The pail is suspended above the water level 3 – 6 inches. In high odor conditions a pail is suspended in each chamber. For severe odor conditions call for technical support...

FOR AIR HANDLERS of ALL SIZES:

Remove the lid off the pail in order to begin activation of **AIR WASH**. The size of the air handler, air flow, building condition and severity of foul odor will determine the number of pails needed. Placement of the pails may affect how quickly odors and fumes are absorbed.

STORAGE:

Store product in a cool, dry area of 75° or less for optimum product life.