

An aggressive floor finish, re-emulsifier and extra heavy duty stripper. Designed for use in heavy build-up areas that have been hardened by high speed burnishing, **Express Strip** can be used with either machine scrubbing, or mop on, vacuum off, techniques. **Express Strip** quickly and effectively penetrates and liquefies multiple coats of burnished finish from vinyl, vinyl composition, linoleum, rubber, cork, marble, ceramic, quarry tile and concrete. **Express Strip** is the ideal product for the removal of acrylic and urethane containing water-based seals. **Express Strip** is also an extremely effective degreaser for removing heavy protein soils, fat, and petroleum based oils and grease from any flooring surface.

**WARNING:** Avoid contact with skin and eyes. May cause severe eye and skin irritation. Harmful if swallowed. Protective eyewear and rubber gloves should be worn when handling. **FIRST AID:** In case of skin contact wash affected area thoroughly with water, and use vinegar if available. If blistering is apparent or irritation persists, call a physician. In case of eye contact flush with water for at least 15 minutes. If irritation continues seek medical assistance. If swallowed, give citrus juice if person is conscious. Get immediate medical aid.

HMIS RATING	
HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	8

P.I.N. J140

**For Professional Use**

**Net Contents:**

**55 Gallons**

**5 Gallons**



# Express Strip

**Fast Acting - Emulsifying Floor Stripper/Degreaser**

**CAUTION: KEEP OUT OF REACH OF CHILDREN. HARMFUL IF SWALLOWED, USE WITH ADEQUATE VENTILATION. AVOID BREATHING SPRAY MISTS. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE CONTAINER. AVOID SKIN & EYE CONTACT. MAY IRRITATE SKIN AND DAMAGE EYES. WEAR EYE PROTECTION**

**DOT HAZMAT SHIPPING INFORMATION:**

**UN 1760, COMPOUND, CLEANING, LIQUID, (CONTAINING SODIUM HYDROXIDE), 8, PG III**

**DIRECTIONS FOR USE:**

**Mop On/Vacuum Off Stripping: Express Strip** may be diluted with hot, cold, hard or soft water for use. The amount of the solubilizer for each stripping job will depend upon the amount of finish build-up on the floor.

**Extra Heavy Duty to Medium Build-Up:** 32 ounces of Express Strip to 1 gallon of warm water.

**Medium Build-Up:** 21 ounces of Express Strip to 1 gallon of warm water.

**Light Build-Up:** 16 ounces of Express Strip to 1 gallon of warm water.

Apply diluted **Express Strip** liberally to the floor, using an area small enough to complete in 20-30 minutes (to avoid drying). Allow **Express Strip** to stand for 5 minutes, then pick up the liquefied finish with a squeegee equipped wet vacuum. After liquefied finish has been removed rinse the floor thoroughly with clear water and wet vacuum.

**Floor Machine Stripping or Degreasing Systems:**

**For Normally Maintained Finishes:** Use 6-8 ounces of Express Strip to one gallon of warm water.

**For High Speed Burnished Finishes:** Use 21-32 ounces of Express Strip to one gallon of warm water. Follow the manual directions above, except agitate well with a floor machine equipped with a stripping pad and remove dissolved finish with a wet vacuum, then rinse thoroughly.



**Encore Industrial Products, LLC**  
 P.O. Box 941119  
 Houston, TX 77094  
 281-944-4777  
 Or 1-877-703-3044  
[www.encoreindustrial.com](http://www.encoreindustrial.com)  
**FOR PROFESSIONAL USE ONLY**