

Directions for Use

Light Duty Cleaning: 2-5oz Fleet Wash per 5 gallons of water.

Medium Duty Cleaning: 8-12oz Fleet Wash per 5 gallons of water.

Heavy Duty Cleaning: 14-20oz Fleet Wash per 5 gallons of water.

For automatic vehicle wash systems, **Fleet Wash** can be diluted up to 320 : 1 for light road dust. Add more product to accommodate the specific needs and application.

HMIS Codes	
Health	1
Flammability	0
Reactivity	0
Personal Protection	B

P.I.N - A – 115



COMPLETELY BIODEGRADABLE
PHOSOPHATE FREE • NEUTRAL pH
SAFE ON CLEAR COAT
STRONG ENOUGH TO REMOVE INSECT BUILD UP
HIGH FOAMING
TIME SAVING WASH-N-WAX FORMULA
GENTLE ON PAINTED SURFACES
REMOVES INDUSTRIAL ROAD FILM

Keep Out of Reach of Children

Net Continance:

- 55DR
- 35DR
- 20DR
- 5GLP

Encore Industrial Products, LLC
PO Box 941119, Houston, TX 77094
281-944-4777 or 1-877-703-3044

Fleet Wash is a High Foaming Concentrate. Apply as desired, rinse off. Dirt, grime and road film disappear leaving the vehicle sparkling clean. **Fleet Wash** will enhance vehicle appearance while protecting the finish.

First Aid Information

Read MSDS for complete information

Eye Contact – Flush eyes with clean water for at least 15 minutes. If irritation occurs call a physician.

Skin contact – Wash skin with soap and water, if irritation occurs, call a physician.

Ingestion – Do not induce vomiting and give large quantities of water. Call a physician immediately if stomach pains or nausea occur.

To reorder call:
1-877-703-3044 or 281-944-4777

