

For Grease Tubes – Follow directions on grease gun for loading instructions. To insure proper service pump out any existing grease prior to applying or pumping **Encore Industrial's Green Tek High Impact Grease.**

For Pails & Drums – Follow directions indicated on the grease pump for proper use.

Appearance	Green, tacky,
smooth	
NLGI	2.5
Penetration	245-265
(ASTM D217)	
Worked Penetration	245-265
60x (ASTMD217)	
Base oil	Mineral oil
Base viscosity	143 cSt at 100°C
Base oil viscosity	11 cSt at 40°C
Base oil viscosity index	40
Base oil pour point	-10°F (-23°C)
Thickener	Inorganic
Additives	EP, antioxidant
and corrosion inhibitors	
Specific gravity	0.9
Density (lb/gal)	7.5
Dropping point	>500°F (260°C)
(ASTM D566)	
Flash point	>400°F (200°C)
Temperature range	0°F – 450°F (-
18°C - 232°C)	
Four-ball EP weld point	315 kgf
(ASTM D2596)	



GREEN TEK

High Impact Grease

Timken Load – 65
 NLGI Rating – 2.0-2.5
 Temperature Rating – 500+ Degrees (Non-Melt)
 Extreme Tacier Package – Excellent Adhesive & Cohesive Properties
 Penetration (ASTM – D – 217) - 245-265 mm
 4-ball weld test – 315 minimum
 Water Resistance – Excellent
 Extreme Pressure Rated – Extreme PSI Rating

OFFSHORE RATED

Keep Out of Reach of Children

Net Wt. 5LB

Green Tek High Impact Grease provides high impact protection. This product helps resist against “pound out”, “splatter out” from vibration and jarring.

First Aid Information

Read SDS for complete information

Eye Contact – Flush eyes with clean water for at least 15 minutes. If irritation occurs call a physician. **SkinContact** – Wash skin with soap and water, if irritation occurs, call a physician.

Ingestion – Do not induce vomiting and give large quantities of water. Call a physician immediately if stomach pains or nausea occur.

MADE IN THE USA

P.I.N - G – 160

Encore Industrial Products, LLC
 PO Box 300, Barker, TX 77413
 281-944-4777 or 1-877-703-3044