

**HIGH GEAR 80W-90  
INDUSTRIAL GEAR LUBRICANT**

Ideal for industrial applications. Provides trouble free performance in high pressure high output industrial configurations. Helps eliminate sludge build up caused by heat. Designed to separate from water quickly to safeguard against etching acids or corrosives.

**P.I.N. G-240**

Health	1
Flammability	1
Reactivity	0
Personal	B

Batch Number: #



**Encore Industrial Products, LLC**  
3502 Bacor Rd., Houston, Tx 77084  
281-944-4777 / 1-877- 703-3044  
[www.encoreindustrial.com](http://www.encoreindustrial.com)



**Oxidation Stabilizers**  
**Extend Service Life**  
**Inhibits Rust & Corrosion**  
**Enhanced with Anti-Wear Additives**  
**Meets GL-5 API Service Specs**  
**Resists Deposit Formation**  
**Protects Seals from Premature Wear**

Keep Out Of Reach of Children

**Net Contents**

- 5 Gallons    20 Gallons  
 30 Gallons    55 Gallons

**First Aid**

**Inhalation:** Vapors generated at high temperatures (only) or oil mist may cause mild irritation of the nose, throat and respiratory system. Consult physician and poison control immediately.

**Eye Irritation:** May cause minimum eye irritation. Consult physician and poison control immediately.

**Skin Contact:** May cause minimum skin irritations, long term heavy exposure may dry or defat the skin. May also cause dermatitis or oil acne. High pressure injection under the skin could cause extensive tissue damage. Consult physician and poison control immediately.

**Ingestion:** If swallowed may be slightly toxic. Consult physician and poison control immediately.

Dispose of in accordance with local, state and federal regulations.



Warning: Harmful if inhaled. Avoid breathing dust/fumes/gas/mist/spray. Use only outdoors or in a well-ventilated area.