

Directions for Use

For Grease Tubes – Follow directions on grease gun for loading instructions. To insure proper service pump out any existing grease prior to applying or pumping **Encore Industrial's Heat Tek Extreme High Temp Grease**.

For Pails & Drums – Follow directions indicated on the grease pump for proper use.

HMIS Codes	
Health	0
Flammability	1
Reactivity	0
Personal Protection	B

P.I.N - G – 145



**HEAT TEK
EXTREME HIGH TEMP
GREASE**

Effective Service Range Above 900° F
Proprietary Synthetic Base to resist extreme high temperatures

Effective Service Range below -20° F
Ideal for extreme service applications

Keep Out of Reach of Children

Net Contents: 14 oz

Encore Industrial Products, LLC
PO Box 300 Barker, TX 77413
281-944-4777 or 1-877-703-3044

Heat Tek's proprietary formulation is the ideal lubricant for most extreme temperature applications. Great high temperature resistance and low temperature resistance make **Heat Tek** uniquely suited for virtually any geographic area.

First Aid Information

Read MSDS for complete information

Eye Contact – Flush eyes with clean water for at least 15 minutes. If irritation occurs call a physician.

Skin contact – Wash skin with soap and water, if irritation occurs, call a physician.

Ingestion – Do not induce vomiting and give large quantities of water. Call a physician immediately if stomach pains or nausea occur.

To reorder call:

1-877-703-3044 or 281-944-4777

